

PD-183



- ▶ 4 ½ digit, 19999 counts display
- ▶ Auto power off
- ▶ Input warning detects wrong
- ▶ Overload protections
- ▶ Frequency & Capacitance
- ▶ Duty Cycle
- ▶ Safety input jacks & test leads
- ▶ Safety rules: IEC 1010-1, CAT III 1000 V
- ▶ Anti shock holster

TRUE RMS

UP TO 20 A !

SPECIFICATIONS	PD-183
Voltage	
DC Volts	200 mV, 2 V, 20 V, 200 V, 1000 V ± 0.05%
AC Volts	200 mV, 2 V, 20 V, 200 V, 750 V ±1% (50 ~ 2 kHz)
Current	
DC Current	200 μA, 2 mA, 20 mA, 200 mA, 20 A ± 0.5 %
AC Current	200 μA, 2 mA, 20 mA, 200 mA, 20 A ± 1.2% (50 ~ 1 kHz)
Resistance	200 Ω, 2 kΩ, 20 kΩ, 200 kΩ, 2 MΩ, 20 MΩ ± 0.15 %
Frequency	2 kHz, 20 kHz, 200 kHz ± 0.5%
Duty Cycle	0 to 90%. 40 Hz to 20 kHz ±2 %
More features	Continuity test, Diode test, Logic test, DATA hold
Resolution	10 μV, 0.01 μA, 0.01 Ω, 0.1 Hz

